



Rental Grade Unit

MLG15 - 15kW Mitsubishi



TOUGH

- STEEL, LOCKABLE ENCLOSURE
- FULL TUBULAR STEEL FRAME
- DURABLE POWDER COAT FINISH

RELIABLE

- KEY SWITCH ON SINGLE PHASE
- MICROPROCESSOR ON THREE PHASE
- LOW OIL / HIGH TEMP SHUTDOWNS
- START LIMIT MAIN BREAKER
- UP TO 60 HOURS FULL LOAD RUN TIME
- 1 YEAR 1,000 HOUR WARRANTY

EASY TO USE

- SELF-PRIMING ENGINES
- EXTERNAL CONVENIENCE OUTLETS WITH INDIVIDUAL BREAKERS
- EXTERNAL EMERGENCY STOP SWITCH
- THREE PHASE MODELS ALSO HAVE VOLTAGE SELECTOR SWITCH, LUGS AND LUG BOX SAFETY SWITCH, AND AUTOMATIC REMOTE START

Rental Grade Unit

MLG15 - 15kW Mitsubishi

| | |
|--|--------------------------|
| Output | |
| 3 Phase - Standby (kW/kVa) | NA |
| Amps (480/208 V) | NA |
| 3 Phase - Prime (kW/kVa) | NA |
| Amps (480/208 V) | NA |
| 1 Phase - Standby (kW/kVa) | 15/15 |
| Amps (240 V) | 62 |
| 1 Phase - Prime (kW/kVa) | 13/13 |
| Amps | 59 |
| AC Voltage - 1 Phase | 120/240 |
| AC Voltage - 3 Phase | NA |
| Frequency Hz. | 60 |
| Power Factor | 1.0 (1 Phase) |
| Generator (Brand/Type/Insulation) | Marathon / Brushless / H |
| Sound (dB(A) 23 Feet @ Prime) | 66 |
| Size & Weight | |
| Skid Mounted (L x Wx H) | NA |
| Dry Weight lb. (kg.) | NA |
| Operating Weight lb. (kg.) | NA |
| Trailer Mounted (L x W x H) (in.) | 105 x 67 x 56 |
| Dry Weight lb. (kg.) | 1380 (625) |
| Operating Weight lb. (kg.) | 1810 (820) |
| Engine | |
| Brand | Mitsubishi |
| Aspiration | Natural |
| HP (Prime @ 1800 rpm) (kWm) | 22 (16.6) |
| Displacement C.I.D. (l.) | 107 (1.8) |
| Cylinders | 4 |
| Speed (rpm) | 1800 |
| Fuel Consumed (Prime gal. (l.)/h) | 1.2 (4.6) |
| Battery (12 volt) | 1 - 12V/720 CCA |
| Capacities | |
| Fuel Tank gal.(l.) | 56 (212) |
| Approximate Run Time (hrs.) | 46 |
| Coolant qt. (l.) | 11.6 (11.0) |
| Oil qt. (l.) | 6.7 (6.3) |
| AC Distribution | |
| Main Breaker | 70 |
| Voltage Selection | None |
| Voltage Regulation | +/-1% |
| 120V - 20 Amp GFI Duplex | 2 |
| 240V - 30 Amp Twist Lock | 2 |
| 240V - 50 Amp Twist Lock | 2 |
| Trailer | |
| Number of Axles & Capacity (lbs.) | 1 (3500) |
| Tire Size (in.) | 15 |
| Brakes | None |
| Hitch | 2" Ball / 3" Ring |